



CHIR-AYU CONTROLS PVT. LTD.

CONSTRUCTION MATERIALS TESTING EQUIPMENT

A1525 SOLO

Regd. Office : 224/1, GIDC, Makarpura, Vadodara-390010. Gujarat, India. **M :** + 91 7878758606

E : sales@chirayugroup.in **W :** www.chirayugroup.in **GSTIN :** 24AAECC9611Q1ZA **PAN No :** AAECC9611Q

CONTROLS



A compact, ergonomic and easy to handheld Phased Array unit based on Total Focusing Method for easy-going imaging of inspection objects with two-dimensional and three-dimensional visualization and evaluation of inspection results.

The instrument has ultra-compact design and is performed in lite-weight shockproof plastic housing. 800-gram weight allows one hand operation in hardly accessible locations. The Multi-SAFT image reconstruction technology offers unique flaw detection capability and extraordinary spatial resolution. Additional imaging and analysis functionality is provided by included INTROVIEW visualization software.

The instrument is equipped with two phased array transducers suitable for most of the regular ultrasonic weld testing. Additional transducers can be purchased for casting and forging inspection.



A1525 SOLO



SPECIFICATION

Phased Array data processing technique	Total Focusing Method
Number of array elements / channels	16
Operation frequencies	1,0; 1,8; 2,5; 4,0; 5,0; 7,5; 10 MHz
Dynamic range	100 dB
Display resolution / type	640 x 480 / TFT
Operation time with battery, not less than	6 h
Dimensions of the electronic unit	260 x 157 x 43 mm
Weight of the electronic unit	0.8 kg

Operation temperature -10 to +55 °C

FEATURES

A1550 Solo covers most of the regular metal inspection tasks, such as:

- Manual and semi-mechanized ultrasonic weld testing including B, C & D-Scan visualization and 3D imaging (by purchasing ACS pipe scanner)
- Testing of small-diameter pipes
- Testing of casting and forging parts
- Tomographic visualization of the inspection volume and accurate flaw sizing

DELIVERY KIT

71525 SOLO – TFM ultrasonic flaw detector – tomograph

- Phased Array transducer M9065 (4 MHz shear wave, pitch 2.5 mm)
- Phased Array transducer 79170 (4 MHz shear wave, pitch 1.6 mm)
- LEMO 00 – LEMO 00 single cable 1,2 m
- USB A – Mini B cable
- Power adaptor with cable
- Ultrasonic Couplant, bottle 4 oz.
- Soft cover
- Hard case



